



ARLON

▶ DPF 303 Banner

Digital Print Super Smooth, Scrim PVC Banner

DPF 303 is a 13-oz white, super smooth, scrim PVC banner with blackout features. This calendared vinyl provides superior print resolution and image quality on both sides of the banner. The scrim is undetectable, whether it is printed or unprinted. This banner is excellent for graphics that will be viewed at a close distance. DPF 303 is rated for outdoor durability up to 1 year (unprinted). Printed durability is dependent on the ink system used.

APPLICATIONS & FEATURES

- Digital printing with a wide variety of direct print systems.
- Merchandising and display graphics.
- Shorter-term banner applications.

PERFORMANCE & PHYSICAL DATA

| PROPERTY | TEST METHODS |
|------------------------------------|------------------------------------------------------------------------------------------------|
| THICKNESS | 13-mil (325 microns) |
| CONSTRUCTION | 13 oz. flexible, polyester scrim banner yarn |
| YARN (DENIER) | 250 x 250 Denier |
| THREAD COUNT | 36 x 36 |
| GLOSS (GLOSS METER 60° REFLECTION) | Matte 0 - 10 Gloss Units Gloss > 40 Gloss Units |
| OPACITY | 100% |
| TENSILE STRENGTH (WARP / WEFT) | 120 / 150 lbf/in |
| TEAR STRENGTH (WARP, WEFT) | 26 / 26 lbf/in |
| SERVICE TEMPERATURE RANGE | 14°F to 122°F (-10°C to 50°C) |
| SHELF LIFE | 1 year from factory shipment. (Free from excessive moisture, temperature, and direct sunlight) |
| STORAGE TEMPERATURE | 85°F or lower |
| SOLVENT RESISTANCE | Resistant to salts, mild acids, and alkalies |
| FIRE RESISTANCE | NFPA 701 Test 2 |
| PRINTABILITY | Standard solvent, eco-solvent, and UV digital inks |

**Standard Terms & Conditions Apply*

TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.