





DPF 8200 HIGH TACK

DPF 8200 High Tack is the ultimate premium film for textured surfaces and installations on demanding surfaces. A durable film combined with a low shrink, high tack adhesive formula that allows for greater dimensional stability - making it easier to apply. With reduced converting and printing time, you can remain focused producing brilliant graphics. Adding heat to the DPF 8200 High Tack when installing on textured surfaces will make your graphic conform to slight contours and textures without any hassle.

Unique Features:

- ▶ Enhanced Dimensional Stability
- Easy to Convert, Print, and ApplyOptimizing your Workflow
- ▶ Low Shrink Adhesive System
- Strong Adhesion for Demanding Applications





Applications:

- ▶ Brick
- ▶ Concrete / Tile
- ▶ Wood / Plastic / Metal
- ▶ Smooth painted / Unpainted walls
- ▶ Decals
- ▶ General Signage

Categories:

- ▶ Exterior Wall Graphics
- ▶ Commercial Graphics

Performance & Physical Data	
Finish:	Satin
Durability (Unprinted):	7 Years
Roll Widths:	1.37 m, 1.52 m, 1.6m
Roll Lengths:	45.72 m
Adhesive:	High Tack, Permanent (Clear)
Release Liner:	Lay-Flat Polycoated
Ink Compatibility:	Eco-Solvent Solvent UV Latex
Compatible Overlaminate:	★Series 3220 ★Series 3420 ★ProTec Series 3960 Series 3210 Series 3310 Series 3350

USA

- a 200 Boysenberry Lane, Placentia, CA 92870
- p 800 232 7161/+1 714 985 6300
- f +1 714 985 6305

EUROPE

- a Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- P +31 70 354 4311
- **f** +31 70 355 7721

CHINA

- a No. 1989 Xinchang Road, Weifang, Shandong, 262400
- P +86 0536 6226568

arlon.com