



ARLON

SLIP RESISTENT OVERLAMINATES

Take advantage of another graphic opportunity that is literally at your feet! Series 3220 Gloss, Series 3420 Gloss & Matte, and Series 3510 Matte are now approved under the UL 410 and EN 14041:2018 regulation for slip-resistance as an interior floor graphic material. Pair it with Arlon DPF 4600GLX/MLX, DPF 8000™ Ultra Tack, DPF 8200 High Tack, or DPF 510GT/MT/GTR/MTR to protect your interior floor graphics.

To learn more about UL, visit: UL.com. To learn more about the EN European Standard, visit: <http://www.en-standard.eu>.

Unique Features:

- ▶ Meets the requirements for slip-resistance on floors for both UL 410 & EN 14041:2018
- ▶ Go-to overlaminate with multiple uses

Recommended Surfaces:

- ▶ Smooth Floors
- ▶ Low-Profile Carpet *

Floor Graphic Details	
UL 410 Certified:	Series 3220G Series 3420G
EN 14041:2018	Series 3420M Series 3510M
Compatible Media:	DPF 4600GLX / MLX DPF 8000™ Ultra Tack DPF 8200 High Tack * DPF 510GT/MT DPF 510GTR/MTR
Recommended Interior Surfaces:	Waxed vinyl flooring Sealed concrete Marble Ceramic tile Sealed wood Terrazzo Low-pile commercial-grade carpet *



* For interior floor graphics on carpet, Arlon recommends DPF 8200 High Tack only

USA

- a** 200 Boysenberry Lane, Placentia, CA 92870
- p** 800 232 7161 / +1 714 985 6300
- f** +1 714 985 6305

EUROPE

- a** Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p** +31 70 354 4311
- f** +31 70 355 7721

CHINA

- a** No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p** +86 0536 6226568

arlon.com

June 2020